

Section VII. Technical Specifications

Bidders must state “**Comply**” in the column “**Statement of Compliance**” against each of the individual parameters of each “Specifications.”

Description	Statement of Compliance
<p>Supply and Delivery of PANP Equipment for The Presidential Communications Office (PCO) (Procurement / Contract No. 2023-PCO-026)</p> <p>Item 1. Core Switch 48 port, brand new Complies with the following minimum requirements: Qty: Two (2) units</p> <p>Description Brand-new and stackwise Port: 48 x Gigabit Ethernet Network, stackwise Height: at least 1.73” Width: at least 17.5” Form Factor: Rack Mount Switch Type: Managed Product Type: Ethernet Switch Network Technology: 10/100/1000Base-T Switching capacity and stacking: 736 Gbps (256 Gbps, 480 Gbps) Total no of MAC addresses: 32,000 Multi-cast routing scale: 8,000 Forwarding Rate with stacking: 547 Mpps DRAM and Flash Memory: 8GB, 16GB Packet Buffer: 16 MB No of VLANs Supported: 4,000 Support dual redundant power supplies: Yes Fan: Yes Warranty: at least 1 year Must have a high performance advanced layer 3 modular switch with virtual switching framework stacking, low latency, resiliency and supports the IEEE 802.1 AVB standard..</p> <p>Features</p> <p>Basic Requirement: 1. Supply delivery, installation, commissioning, 8*5 phone, Email, On-site Support/Technical assistance and Knowledge Transfer.</p>	

<p>2. The proposed core switches should have full functional compatibility with the current equipment installed at site: DVB, idirect, C9200L.</p> <p>3. The Supplier shall facilitate the removal of the existing core Switches (C3750G), migration and configuration of the switches offered.</p>																									
<p>Item 2. Access Switch 24 port, brand new Complies with the following minimum requirements: Qty: Two (2)</p> <table border="0"> <tr> <td>Port:</td> <td>24 x Gigabit Ethernet Network, 4*1G SFP</td> </tr> <tr> <td>Switching capacity</td> <td>56 Gbps</td> </tr> <tr> <td>Forwarding Rate</td> <td>41 Mpps or higher</td> </tr> <tr> <td>Form Factor:</td> <td>Rack Mount</td> </tr> <tr> <td>Switch Type:</td> <td>Managed</td> </tr> <tr> <td>Product Type:</td> <td>Ethernet Switch</td> </tr> <tr> <td>Network Technology:</td> <td>10/100/1000Base-T</td> </tr> <tr> <td>Interface:</td> <td>Web based GUI</td> </tr> <tr> <td>warranty:</td> <td>at least 1 Year</td> </tr> <tr> <td>Defense Mechanism:</td> <td>ARP, port security, Time-based ACL and rate limit based to block unauthorized devices, DOS, STP provides protection against loops by transmitting loop protocol packets out of ports to prevent network faults caused by loops generated by the connection of unauthorized devices</td> </tr> <tr> <td>Others:</td> <td></td> </tr> <tr> <td>Support:</td> <td>8*5 phone,email, chat support and Knowledge Transfer.</td> </tr> </table>	Port:	24 x Gigabit Ethernet Network, 4*1G SFP	Switching capacity	56 Gbps	Forwarding Rate	41 Mpps or higher	Form Factor:	Rack Mount	Switch Type:	Managed	Product Type:	Ethernet Switch	Network Technology:	10/100/1000Base-T	Interface:	Web based GUI	warranty:	at least 1 Year	Defense Mechanism:	ARP, port security, Time-based ACL and rate limit based to block unauthorized devices, DOS, STP provides protection against loops by transmitting loop protocol packets out of ports to prevent network faults caused by loops generated by the connection of unauthorized devices	Others:		Support:	8*5 phone,email, chat support and Knowledge Transfer.	
Port:	24 x Gigabit Ethernet Network, 4*1G SFP																								
Switching capacity	56 Gbps																								
Forwarding Rate	41 Mpps or higher																								
Form Factor:	Rack Mount																								
Switch Type:	Managed																								
Product Type:	Ethernet Switch																								
Network Technology:	10/100/1000Base-T																								
Interface:	Web based GUI																								
warranty:	at least 1 Year																								
Defense Mechanism:	ARP, port security, Time-based ACL and rate limit based to block unauthorized devices, DOS, STP provides protection against loops by transmitting loop protocol packets out of ports to prevent network faults caused by loops generated by the connection of unauthorized devices																								
Others:																									
Support:	8*5 phone,email, chat support and Knowledge Transfer.																								
<p>Item 3. Access Switch 48 port, brand new Complies with the following minimum requirements: Qty: Two (2) units</p> <table border="0"> <thead> <tr> <th></th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Port:</td> <td>48 x Gigabit Ethernet Network, 4*1G SFP</td> </tr> <tr> <td>Switching capacity</td> <td>104 Gbps or better</td> </tr> <tr> <td>Forwarding Rate</td> <td>77 Mpps</td> </tr> <tr> <td>Buffer size:</td> <td>1.5 MB or higher</td> </tr> <tr> <td>Form Factor:</td> <td>Rack Mount</td> </tr> <tr> <td>Switch Type:</td> <td>Managed</td> </tr> </tbody> </table>		Description	Port:	48 x Gigabit Ethernet Network, 4*1G SFP	Switching capacity	104 Gbps or better	Forwarding Rate	77 Mpps	Buffer size:	1.5 MB or higher	Form Factor:	Rack Mount	Switch Type:	Managed											
	Description																								
Port:	48 x Gigabit Ethernet Network, 4*1G SFP																								
Switching capacity	104 Gbps or better																								
Forwarding Rate	77 Mpps																								
Buffer size:	1.5 MB or higher																								
Form Factor:	Rack Mount																								
Switch Type:	Managed																								

<p>Product Type: Ethernet Switch</p> <p>Network Technology: 10/100/1000Base-T</p> <p>Interface: Web based GUI</p> <p>warranty: at least 1 Year</p> <p>Security: ARP, IP Source Guard, Mac/Port and IP Binding, port security , Time-based ACL, rate limit based to block unauthorized devices , DOS, STP</p> <p>Loopback Detection: provides protection against loops by transmitting loop protocol packets out of ports to prevent network faults caused by loops generated by the connection of unauthorized devices</p> <p>Support: 8*5 phone,email, chat support and Knowledge Transfer.</p> <p>Others: Must be the same brand with the 24-port</p>	
<p>Item 4. Uninterruptible Power Supply (UPS), brand new</p> <p>Complies with the following minimum requirements:</p> <p>Qty: Two (2) units</p> <p>Rating: 1KVA</p> <p>Form Factor: Rack Mount or Tower Type</p> <p>Technology: Monitors power conditions and regulates voltage and frequency to protect Equipment</p> <p>Output Voltage: 220/230/240V</p> <p>Input frequency range: 40Hz-70Hz, 50/60 Hz</p> <p>Operating temperature: 0 to 40°C</p> <p>Noise level: <37 dB or <40 @ typical load</p> <p>Communication Ports: 1 USB port,1 RS232 serial port</p> <p>Warranty: at least 1 year</p>	

Item 5. ICT Software Complies with the following minimum requirements: Qty: 1 Lot																																				
	Must be compatible with the existing HP Proliant DL180 G9 8SFF Intel Xeon Processor E5-2609V3 (1.90 Ghz/6-core)/64GB System memory.																																			
Windows Server Software (Latest)	Must be compatible with sunfire 4200 audio server software Device/User CAL Running Apps: IceCast, XAMPP Control Panel v3.2.1																																			
hardware and service warranty	at least 1 year																																			
Item 6. Tools and materials, brand new Complies with the following minimum requirements:																																				
	<table border="0"> <thead> <tr> <th style="text-align: left;">Description</th> <th style="text-align: right;">QTY</th> </tr> </thead> <tbody> <tr> <td>Cat 5e 305m/roll</td> <td style="text-align: right;">2</td> </tr> <tr> <td>RJ45 connector /pc</td> <td style="text-align: right;">1000</td> </tr> <tr> <td>RJ11 connector/ pc</td> <td style="text-align: right;">200</td> </tr> <tr> <td>RJ12 connector/ pc</td> <td style="text-align: right;">100</td> </tr> <tr> <td>RJ9 connector/ pc</td> <td style="text-align: right;">100</td> </tr> <tr> <td>rubber boots Red-500 pcs</td> <td style="text-align: right;">1</td> </tr> <tr> <td>rubber boots Blue-500 pcs</td> <td style="text-align: right;">1</td> </tr> <tr> <td>Battery 9V/pc</td> <td style="text-align: right;">5</td> </tr> <tr> <td>rechargeable Flashlight/pc</td> <td style="text-align: right;">2</td> </tr> <tr> <td>rubber tape/ pc</td> <td style="text-align: right;">10</td> </tr> <tr> <td>electrical tape/ Pc</td> <td style="text-align: right;">10</td> </tr> <tr> <td>Safety Gloves (electrical)/ pair</td> <td style="text-align: right;">10</td> </tr> <tr> <td>12" Self-Locking Stainless Steel Zip Cable Tie (100pcs/pack) Size: 4.6x300m</td> <td style="text-align: right;">2</td> </tr> <tr> <td>Handheld Label Printer machine with label printer tape/unit</td> <td style="text-align: right;">1</td> </tr> <tr> <td>Paint with Primer for metal /Gallons (color white) , 2" Paint Brush</td> <td style="text-align: right;">2</td> </tr> <tr> <td>Soldering iron kit, 60W soldering gun, solder iron kit welding tool, adjustable temperature from 200 to 450°C, 5 soldering iron tips,</td> <td style="text-align: right;">1</td> </tr> </tbody> </table>	Description	QTY	Cat 5e 305m/roll	2	RJ45 connector /pc	1000	RJ11 connector/ pc	200	RJ12 connector/ pc	100	RJ9 connector/ pc	100	rubber boots Red-500 pcs	1	rubber boots Blue-500 pcs	1	Battery 9V/pc	5	rechargeable Flashlight/pc	2	rubber tape/ pc	10	electrical tape/ Pc	10	Safety Gloves (electrical)/ pair	10	12" Self-Locking Stainless Steel Zip Cable Tie (100pcs/pack) Size: 4.6x300m	2	Handheld Label Printer machine with label printer tape/unit	1	Paint with Primer for metal /Gallons (color white) , 2" Paint Brush	2	Soldering iron kit, 60W soldering gun, solder iron kit welding tool, adjustable temperature from 200 to 450°C, 5 soldering iron tips,	1	
Description	QTY																																			
Cat 5e 305m/roll	2																																			
RJ45 connector /pc	1000																																			
RJ11 connector/ pc	200																																			
RJ12 connector/ pc	100																																			
RJ9 connector/ pc	100																																			
rubber boots Red-500 pcs	1																																			
rubber boots Blue-500 pcs	1																																			
Battery 9V/pc	5																																			
rechargeable Flashlight/pc	2																																			
rubber tape/ pc	10																																			
electrical tape/ Pc	10																																			
Safety Gloves (electrical)/ pair	10																																			
12" Self-Locking Stainless Steel Zip Cable Tie (100pcs/pack) Size: 4.6x300m	2																																			
Handheld Label Printer machine with label printer tape/unit	1																																			
Paint with Primer for metal /Gallons (color white) , 2" Paint Brush	2																																			
Soldering iron kit, 60W soldering gun, solder iron kit welding tool, adjustable temperature from 200 to 450°C, 5 soldering iron tips,	1																																			
Cables, Boots, Connectors and other materials																																				
Soldering iron kit																																				

<p>Crimping tool Kit</p> <p>Crimper Tools for RF Connector</p>	<p>solder wire(3 rolls), solder paste (1 pc), sponge for soldering and repair, silicon paste (1 pc)</p> <p>RJ45 Crimping Tool Kit Ethernet Crimp Tool Set, RJ-11(6P4C), RJ-12 (6P6C), 8P/RJ-45 (8P8C), RJ9(4P4C) Crimp, Cut and Strip Tool, All-in-one Multi-Tool for Network Telephone Cat5 Cat5e Cat6 Cat6A Modular Connector Plug Cables with heavy duty wire cutters and strippers (Scissor) Universal Type , Ratchet Coax Crimper Tool for RF connector RG9, RG214</p> <p>2</p> <p>2</p>																	
<p>Item 7. IP Phone, brand new Complies with the following minimum requirements: QTY: Ten (10) units</p> <table border="0" data-bbox="172 985 1197 1563"> <thead> <tr> <th></th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Interface:</td> <td>Gigabit Ethernet (10/100/1000)</td> </tr> <tr> <td>Mount:</td> <td>Stand, wall-mount</td> </tr> <tr> <td>Supports POE:</td> <td>Yes</td> </tr> <tr> <td>Features</td> <td>Able to hold, Transfer, conference Full Duplex speakerphone</td> </tr> <tr> <td>Others:</td> <td>PoE Class (IEEE 802.3af) registers as class 1 device and supports 802.3az no End-point license required. This will replace old and defective unit. Must be compatible with the existing IPPBX: Avaya</td> </tr> <tr> <td>Color:</td> <td>Black</td> </tr> <tr> <td>Warranty:</td> <td>at least 1 year</td> </tr> </tbody> </table>				Description	Interface:	Gigabit Ethernet (10/100/1000)	Mount:	Stand, wall-mount	Supports POE:	Yes	Features	Able to hold, Transfer, conference Full Duplex speakerphone	Others:	PoE Class (IEEE 802.3af) registers as class 1 device and supports 802.3az no End-point license required. This will replace old and defective unit. Must be compatible with the existing IPPBX: Avaya	Color:	Black	Warranty:	at least 1 year
	Description																	
Interface:	Gigabit Ethernet (10/100/1000)																	
Mount:	Stand, wall-mount																	
Supports POE:	Yes																	
Features	Able to hold, Transfer, conference Full Duplex speakerphone																	
Others:	PoE Class (IEEE 802.3af) registers as class 1 device and supports 802.3az no End-point license required. This will replace old and defective unit. Must be compatible with the existing IPPBX: Avaya																	
Color:	Black																	
Warranty:	at least 1 year																	
<p>Item 8. Analog Telephone, brand new Complies with the following minimum requirements: QTY: Five (5) units</p> <table border="0" data-bbox="172 1747 1197 2033"> <thead> <tr> <th></th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Color:</td> <td>Black</td> </tr> <tr> <td>Caller ID:</td> <td>Yes</td> </tr> <tr> <td>Phone Type:</td> <td>Corded</td> </tr> <tr> <td>Power source:</td> <td>Corded Electric</td> </tr> <tr> <td>Ringer Volume Control:</td> <td>Off/Low/High</td> </tr> </tbody> </table>				Description	Color:	Black	Caller ID:	Yes	Phone Type:	Corded	Power source:	Corded Electric	Ringer Volume Control:	Off/Low/High				
	Description																	
Color:	Black																	
Caller ID:	Yes																	
Phone Type:	Corded																	
Power source:	Corded Electric																	
Ringer Volume Control:	Off/Low/High																	

others:	No third party End-point license required. This will replace old and defective unit	
warranty:	at least 1 year	
Item 9. Data Cabinet, brand new		
Complies with the following minimum requirements:		
QTY: One (1) unit		
	Description	
Dimension:	Floor Mounted Data Cabinet, 600mm W x 800mm D x 7ftH/42U	
Cage nuts	32 pcs or more	
Exhaus Fan	4 pcs	
PDU:	Power Strip Socket with 8*3-pronged convenient outlets or higher	
Color:	Powder Coated Textured Black Finished or better	
Others:	Plexiglass Front Door with lock & Vented Back Door with Lock 2-vented side panels with lock & louvers with 4 sets adjustable Feet & heavy duty castor wheels rear vertical cable manager with 14 pcs rings	

Conforme:

Full Name and Signature of Bidder/Authorized Rep. : _____

Designation : _____

Name of Company : _____